

Material Safety Data Sheet

GR-132

1. Product and company identification

: GR-132 (Hoppes No. 9 Gun Grease) **Product name**

Material uses : Petroleum lubricating grease

Bushnell : LUBRIPLATE® Lubricants Co. **Distributor** Supplier/Manufacturer 9200 Cody

129 Lockwood St. Newark, NJ 07105

Telephone no.: 1-973-589-9150

06/11/2012. Validation date

Prepared by Atrion International Inc.

CHEM-TEL 1-800-255-3924 (24 hour) In case of emergency

Hazards identification

Physical state : Solid. [grease]

Color : Beige. Odor Mineral oil.

Emergency overview

Signal word : WARNING!

CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. PROLONGED OR **Hazard statements**

> REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL

Overland Park, KC 66214

Telephone no.: 800-423-3537

DATA.

Precautions Do not get in eyes. Avoid contact with skin and clothing. Use only with adequate

ventilation. Keep container tightly closed and sealed until ready for use. Wash

thoroughly after handling.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Dermal contact. Eye contact. Inhalation. Ingestion. **Routes of entry**

Potential acute health effects

Inhalation : Irritating to respiratory system.

: No known significant effects or critical hazards. Ingestion

Skin Irritating to skin. Defatting to the skin.

: Severely irritating to eyes. Risk of serious damage to eyes. **Eves**

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data.

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

No known significant effects or critical hazards. Carcinogenicity

Mutagenicity No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Developmental effects**

: No known significant effects or critical hazards. **Fertility effects**

: Contains material which may cause damage to the following organs: lungs, upper Target organs

respiratory tract, skin, eyes.

Over-exposure signs/symptoms

Inhalation

06/11/2012. **United States/Canada** 1/12

2. Hazards identification

Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion

: No specific data.

Skin

: Adverse symptoms may include the following:

irritation redness dryness cracking

Eyes

: Adverse symptoms may include the following:

pain or irritation

watering redness

Medical conditions aggravated by overexposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

3. Composition/information on ingredients

United States

Name	CAS number	%
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30-60
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	10-30
Zinc oxide	1314-13-2	10-30
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	5-10
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	5-10
Fatty acids, C16-18	67701-03-5	5-10
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	1-5
Quartz (SiO2)	14808-60-7	0.1-1

Canada

Name	CAS number	%
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30-60
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	10-30
Zinc oxide	1314-13-2	10-30
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	5-10
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	5-10
Fatty acids, C16-18	67701-03-5	5-10
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	1-5
Quartz (SiO2)	14808-60-7	0.1-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

First aid measures 4.

Inhalation

Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion

: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician

: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product : No specific fire or explosion hazard.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

Hazardous thermal decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides phosphorus oxides metal oxide/oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	ACGIH TLV (United States, 1/2011). TWA: 5 mg/m³ 8 hour(s). Form: Inhalable fraction NIOSH REL (United States, 6/2009). TWA: 5 mg/m³ 10 hour(s). Form: Mist STEL: 10 mg/m³ 15 minute(s). Form: Mist OSHA PEL (United States, 6/2010). TWA: 5 mg/m³ 8 hour(s).
Distillates (petroleum), hydrotreated light naphthenic	ACGIH TLV (United States, 1/2011). TWA: 5 mg/m³ 8 hour(s). Form: Inhalable fraction NIOSH REL (United States, 6/2009). TWA: 5 mg/m³ 10 hour(s). Form: Mist STEL: 10 mg/m³ 15 minute(s). Form: Mist OSHA PEL (United States, 6/2010). TWA: 5 mg/m³ 8 hour(s).
Zinc oxide	NIOSH REL (United States, 6/2009). CEIL: 15 mg/m³ Form: Dust TWA: 5 mg/m³ 10 hour(s). Form: Dust and fumes STEL: 10 mg/m³ 15 minute(s). Form: Fume OSHA PEL 1989 (United States, 3/1989). TWA: 5 mg/m³ 8 hour(s). Form: Fume STEL: 10 mg/m³ 15 minute(s). Form: Fume TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 10 mg/m³ 8 hour(s). Form: Total dust OSHA PEL (United States, 6/2010). TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 15 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 2 mg/m³ 8 hour(s). Form: Respirable fraction STEL: 10 mg/m³ 15 minute(s). Form: Respirable fraction
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 1/2011). TWA: 5 mg/m³ 8 hour(s). Form: Inhalable fraction NIOSH REL (United States, 6/2009). TWA: 5 mg/m³ 10 hour(s). Form: Mist STEL: 10 mg/m³ 15 minute(s). Form: Mist OSHA PEL (United States, 6/2010). TWA: 5 mg/m³ 8 hour(s).
Distillates (petroleum), hydrotreated light paraffinic	ACGIH TLV (United States, 1/2011). TWA: 5 mg/m³ 8 hour(s). Form: Inhalable fraction NIOSH REL (United States, 6/2009). TWA: 5 mg/m³ 10 hour(s). Form: Mist STEL: 10 mg/m³ 15 minute(s). Form: Mist OSHA PEL (United States, 6/2010). TWA: 5 mg/m³ 8 hour(s).
Quartz (SiO2)	OSHA PEL Z3 (United States, 9/2005). Notes: 250/(%SiO2+5)

8. Exposure controls/personal protection

TWA: 250 mppcf 8 hour(s). Form: Respirable

OSHA PEL Z3 (United States, 9/2005). Notes: 10/(SiO2+2)

TWA: 10 mg/m³ 8 hour(s). Form: Respirable OSHA PEL 1989 (United States, 3/1989).

TWA: 0.1 mg/m³, (as quartz) 8 hour(s). Form: Respirable dust

ACGIH TLV (United States, 1/2011).

TWA: 0.025 mg/m³ 8 hour(s). Form: Respirable fraction

NIOSH REL (United States, 6/2009).

TWA: 0.05 mg/m³ 10 hour(s). Form: respirable dust

OSHA PEL Z3 (United States, 9/2005). Notes: 30/(%SiO2+2)

TWA: 30 mg/m³ 8 hour(s). Form: Total dust.

Canada

Occupational exposure limits		TWA	TWA (8 hours)		STEL (15 mins)		Ceiling				
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
Zinc oxide	US ACGIH 1/2011	-	2	-	-	10	-	-	-	-	[a]
	AB 4/2009	-	2	-	-	10	-	-	-	-	[b]
	BC 9/2011	-	2	-	-	10	-	-	-	-	[b]
	ON 7/2010	-	2	-	-	10	-	-	-	-	[a]
	QC 9/2011	-	5	-	-	10	-	-	-	-	[c]
Quartz (SiO2)	US ACGIH 1/2011	-	0.025	-	-	-	-	-	-	-	[a]
, ,	AB 4/2009	-	0.025	-	-	-	-	-	-	-	[d]
	BC 9/2011	-	0.025	-	-	-	-	-	-	-	[b]
	ON 7/2010	_	0.1	_	-	-	-	-	_	-	[e]
	QC 9/2011	_	0.1	_	-	-	-	-	_	-	[f]
Distillates (petroleum), hydrotreated heavy naphthenic	US ACGIH 1/2011	-	5	-	-	-	-	-	-	-	[9]
	ON 7/2010	-	5	-	-	10	-	-	-	-	[h]
	QC 9/2011	_	5	_	-	10	-	-	_	-	[h]
Distillates (petroleum), hydrotreated light naphthenic	US ACGIH 1/2011	-	5	-	-	-	-	-	-	-	[g]
	ON 7/2010	-	5	-	-	10	-	-	-	-	[h]
	QC 9/2011	-	5	-	-	10	-	-	-	-	[h]
Distillates (petroleum), hydrotreated heavy paraffinic	US ACGIH 1/2011	-	5	-	-	-	-	-	-	-	[g]
	ON 7/2010	_	5	_	-	10	-	-	_	-	[h]
	QC 9/2011	-	5	-	-	10	-	-	-	-	[h]
Distillates (petroleum), hydrotreated light paraffinic	US ACGIH 1/2011	-	5	-	-	-	-	-	-	-	[g]
	ON 7/2010	-	5	-	-	10	-	-	-	_	[h]
	QC 9/2011	-	5	-	-	10	-	-	-	-	[h]

Form: [a]Respirable fraction [b]Respirable [c]fume [d]Respirable particulate [e]Respirable fraction: means that size fraction of the airborne particulate deposited in the gas-exchange region of the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 4 μ m at 50 per cent collection efficiency. [f]Respirable dust. [g]Inhalable fraction [h]mist

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking, using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

8. Exposure controls/personal protection

Respiratory: Use a properly fitted, air-purifying or air-fed respirator complying with an approved

standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Eyes : Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists or

dusts.

Skin : Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before handling

this product.

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state : Solid. [grease]

Flash point : Open cup: 193°C (379.4°F) [Cleveland.]

Auto-ignition temperature : Not available.

Flammable limits : Lower: 0.9%

Upper: 7%

Color : Beige.
Odor : Mineral oil.

pH : Not available.

Boiling/condensation point : >288°C (>550.4°F)

Melting/freezing point : Not available. **Relative density** : 0.94 [Water = 1]

Density: Not available.

Vapor pressure : <0.0013 kPa (<0.01 mm Hg) [20°C]

Vapor density: >5 [Air = 1]VOC content: 0 lbs/gal (0 g/l)Odor threshold: Not available.

Evaporation rate : <0.01 (butyl acetate = 1)

Viscosity : Kinematic (40°C (104°F)): 0.39 cm²/s (39 cSt)(Mineral oil.)

Solubility : Very slightly soluble in the following materials: hot water.

Insoluble in the following materials: cold water.

LogK_{ow} : Not available.

Physical/chemical : Mineral oil.:

properties comments Kinematic viscosity (100 °C (212 °F)): 200 SUS

Pour point: -40 °C (-40 °F)

Stability and reactivity 10.

Chemical stability

: The product is stable.

Conditions to avoid

: No specific data.

Incompatible materials

Reactive or incompatible with the following materials: oxidizing materials and acids. Incompatibility: Chlorine.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

11. **Toxicological information**

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), hydrotreated light naphthenic	LC50 Inhalation Vapor	Rat	2180 mg/m3	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), hydrotreated light paraffinic	LC50 Inhalation Vapor	Rat	3900 mg/m3	4 hours

Chronic toxicity

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Zinc oxide	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
Distillates (petroleum), hydrotreated light naphthenic	Skin - Moderate irritant	Rabbit	-	24 hours 0.5 Mililiters	-

Sensitizer

Not available.

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Distillates (petroleum), hydrotreated heavy naphthenic	A4	-	-	-	-	-
Distillates (petroleum), hydrotreated light naphthenic	A4	-	-	-	-	-
Zinc oxide	A4	-	_	_	-	_
Distillates (petroleum), hydrotreated heavy paraffinic	A4	-	-	-	-	-
Distillates (petroleum), hydrotreated light paraffinic	A4	-	-	-	-	_
Quartz (SiO2)	A2	1	-	+	Proven.	-

11. Toxicological information

Mutagenicity

Not available.

Teratogenicity

Not available.

Reproductive toxicity

Not available.

12. Ecological information

Ecotoxicity

: This material is very toxic to aquatic life with long lasting effects.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Zinc oxide	Acute EC50 0.042 mg/L Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Acute LC50 98 ug/L Fresh water	Daphnia - Daphnia magna - Neonate - <24 hours	48 hours
	Acute LC50 1.1 to 2.5 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

Persistence/degradability

Not available.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN3077	Environmentally hazardous substance, solid, n.o.s. (Zinc oxide). Marine pollutant	9	III	¥2	Limited quantity Yes. Special provisions 8, 146, 335, B54, IB8, IP3, N20, T1, TP33

GR-132						
14. Transport information						
TDG Classification	UN3077	ENVIRONMENTALLY	9	III	A	Explosive Limit and

TDG Classification	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc oxide). Marine pollutant		III	9 MAMRE FOLLUTANT	Explosive Limit and Limited Quantity Index 5 Special provisions 16
IMDG Class	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc oxide). Marine pollutant (Zinc oxide)		III	1 1 1 2 2 2 2 2 3 3 3 4 3 3 4 3	Emergency schedules (EmS) F-A, S-F
IATA-DGR Class	UN3077	Environmentally hazardous substance, solid, n.o.s. (Zinc oxide)	9	III	1 1 1 2 2 2	Passenger and Cargo AircraftQuantity limitation: 400 kg Packaging instructions: 956 Cargo Aircraft OnlyQuantity limitation: 400 kg Packaging instructions: 956 Limited Quantities - Passenger AircraftQuantity limitation: 30 kg Packaging instructions: Y956

PG* : Packing group

15. Regulatory information

United States

HCS Classification

: Irritating material Target organ effects

U.S. Federal regulations

: TSCA 8(a) PAIR: Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts TSCA 8(a) IUR: Not determined

United States inventory (TSCA 8b): Not determined.

SARA 302/304 emergency planning and notification: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: Distillates (petroleum), hydrotreated light naphthenic; Distillates (petroleum), hydrotreated heavy naphthenic; Fatty acids, C16-18; Zinc oxide; Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Distillates (petroleum), hydrotreated heavy paraffinic: Delayed (chronic) health hazard; Distillates (petroleum), hydrotreated light naphthenic: Immediate (acute) health hazard; Distillates (petroleum), hydrotreated heavy naphthenic: Immediate (acute) health hazard; Fatty acids, C16-18: Immediate (acute) health hazard; Zinc oxide: Immediate (acute) health hazard, Delayed (chronic) health hazard; Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts: Immediate (acute) health hazard

Clean Water Act (CWA) 307: Zinc oxide; Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts; zinc bis(dibutyldithiocarbamate)

Clean Air Act (CAA) 112 accidental release prevention: No products were found.

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Not listed

Regulatory information 15.

Clean Air Act Section 602 Not listed

Class I Substances

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

(Essential Chemicals)

: Not listed

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Zinc oxide Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	1314-13-2 68649-42-3	10-30 1-5
Supplier notification	Zinc oxide Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	1314-13-2 68649-42-3	10-30 1-5

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

: The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES, **Massachusetts**

HYDROTREATED LIGHT NAPHTHENIC; MINERAL OIL, PETROLEUM DISTILLATES,

HYDROTREATED LIGHT PARAFFINIC; ZINC OXIDE FUME

: None of the components are listed. **New York**

The following components are listed: MINERAL OIL (UNTREATED and MILDLY **New Jersey**

TREATED); MINERAL OIL (UNTREATED and MILDLY TREATED); MINERAL OIL (UNTREATED and MILDLY TREATED); MINERAL OIL (UNTREATED and MILDLY TREATED); SILICA, QUARTZ; QUARTZ (SiO2); ZINC OXIDE; ZINC compounds

: The following components are listed: QUARTZ (SIO2); ZINC OXIDE (ZNO); ZINC **Pennsylvania**

COMPOUNDS

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	•	•	Maximum acceptable dosage level
Quartz (SiO2)	Yes.	No.	No.	No.

Canada

WHMIS (Canada) : Not controlled under WHMIS (Canada).

Canadian lists

Canadian NPRI : The following components are listed: Zinc; Zinc

: None of the components are listed. **CEPA Toxic substances**

Canada inventory : Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

Regulatory information 15.

International lists

Australia inventory (AICS): Not determined. China inventory (IECSC): Not determined.

Japan inventory: Not determined. **Korea inventory**: Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Chemical Weapons

Convention List Schedule I

Chemicals

: Not listed

: Not listed

Chemical Weapons Convention List Schedule

II Chemicals

Chemical Weapons Convention List Schedule

III Chemicals


: Not listed

16. Other information

Label requirements

: CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910,1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

: 06/11/2012. **Date of issue**

GR-132

16. Other information

Date of previous issue : No previous validation.

Version : 1

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.