

SAFETY DATA SHEET

24-hr Emergency Phone Number
800-255-3924 (Chem-Tel)

SECTION 1 - IDENTIFICATION

Product Identifier(s)	1720	Revision No.	3
Product Name	Cleaner / Degreaser	Revision Date	June 10, 2013
Other Means of Identification	None	Print Date	June 10, 2013
Identified Uses of the Product	Firearms cleaner and degreaser		
Restrictions on Use	No restrictions identified		

MANUFACTURER DETAILS		DISTRIBUTOR DETAILS	
Company Name	Tri-Pac Inc	Company Name	Bushnell
Address	17336 M-60 East Vandalia MI 49095	Address	9200 Cody Overland Park KC 66214
Phone Number	269-476-2303	Phone Number	800-423-3537
Fax Number	269-476-2302	Fax Number	913-752-3570

SECTION 2 - HAZARDS IDENTIFICATION

GHS/CLP (1272/2008) Classification of the Substance or Mixture

HEALTH HAZARDS									
Acute Tox. Oral	<input type="text" value="3"/>	Skin Irritation	<input type="text"/>	Skin Sensitization	<input type="text"/>	Tox. To Reproduction	<input type="text"/>	STOT SE	<input type="text" value="3"/>
Acute Tox. Skin	<input type="text" value="3"/>	Eye Irritation	<input type="text" value="2A"/>	Mutagenicity	<input type="text"/>	Aspiration Hazard	<input type="text" value="1"/>	STOT RE	<input type="text"/>
Acute Tox. Inhalation	<input type="text" value="3"/>	Resp. Sensitization	<input type="text"/>	Carcinogenicity	<input type="text"/>				

PHYSICAL HAZARDS									
Unstable Explosive	<input type="text"/>	Oxidizing Gas	<input type="text"/>	Flammable Solid	<input type="text"/>	Pyrophoric Solid	<input type="text"/>	Oxidizing Solid	<input type="text"/>
Explosive	<input type="text"/>	Gas Under Pressure	<input type="text"/>	Self-Reactive Substance	<input type="text"/>	Emits Flammable Gas	<input type="text"/>	Organic Peroxide	<input type="text"/>
Flammable Gas	<input type="text"/>	Refrigerated Liq. Gas	<input type="text"/>	Pyrophoric Liquid	<input type="text"/>	Oxidizing Liquid	<input type="text"/>	Corrosive to Metal	<input type="text"/>
Aerosol	<input type="text"/>	Flammable Liquid	<input type="text" value="1"/>	Self-Heating Substance	<input type="text"/>				

ENVIRONMENTAL HAZARDS									
Aquatic Acute	<input type="text"/>	Aquatic Chronic	<input type="text"/>	Ozone Depleting	<input type="text"/>				

GHS/CLP (1272/2008) Label Elements

Hazard Pictograms



Signal Word

DANGER

Hazard Statements

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to organs. Toxic if swallowed, in contact with skin or if inhaled.

Precautionary Statements

General

Keep out of reach of children.

SAFETY DATA SHEET

24-hr Emergency Phone Number

800-255-3924 (Chem-Tel)

Prevention	<i>Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosive proof equipment and non-sparking tools. Take precautionary measures against static discharge. Do not breath fumes. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves and eyewear.</i>
Response	<i>IF SWALLOWED: Immediately call a poison center or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Remove contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Seek medical attention immediately.</i>
Storage	<i>Store in a well-ventilated place. Keep containers tightly closed. Keep cool. Store locked up.</i>
Disposal	<i>Dispose of container and contents in an environmentally safe manner.</i>

Other Hazards Which Do Not Result In Classification

Hazards *Not Applicable*

Other Classifications

HMIS III Classification Health: *2 Flammability: 3 Physical Hazard: 0
NFPA Classification Health: 2 Flammability: 3 Reactivity: 0 Special Hazard: None

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

ID	INGREDIENT	CAS NUMBER	EINECS	INDEX NUMBER	% WT
1	<i>Isopropanol</i>	<i>0000067-63-0</i>	<i>200-661-7</i>	<i>603-117-00-0</i>	<i>60 - 100</i>
2	<i>Methanol</i>	<i>0000067-56-1</i>	<i>200-659-6</i>	<i>603-001-00-X</i>	<i>3 - 7</i>

SECTION 4 - FIRST-AID MEASURES

Description of First-Aid Measures

Eye Contact	<i>Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Seek medical attention immediately.</i>
Skin Contact	<i>Remove with soap and water, rinsing and repeating for 15 minutes. Remove contaminated clothing.</i>
Ingestion	<i>Do NOT induce vomiting- Aspiration hazard! Immediately call a poison center or physician. Rinse mouth.</i>
Inhalation	<i>Remove victim to fresh air and keep at rest in a position comfortable for breathing.</i>
First-Aid Responder Protection	<i>Wear adequate personal protective equipment based on the nature and severity of the emergency.</i>

Most Important Symptoms and Effects, Both Acute and Delayed

Eye Contact	<i>Liquid contact may cause severe eye irritation.</i>
Skin Contact	<i>Repeated exposure may cause skin dryness or cracking.</i>
Ingestion	<i>POISON! May be fatal or cause blindness if swallowed. Cannot be made nonpoisonous.</i>
Inhalation	<i>May cause drowsiness or dizziness.</i>

Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	<i>Treat symptomatically.</i>
Specific Treatments/Antidotes	<i>Details on specific treatments and/or antidotes are not available.</i>
Immediate Medical Attention	<i>No information available.</i>

SECTION 5 - FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Extinguishing Media	<i>Water, CO2, dry chemical, or universal aqueous film forming foam</i>
Unsuitable Media	<i>Water jet</i>

Specific Hazards Arising from the Chemical or Mixture

Decomposition Products	<i>Decomposition products may include oxides of carbon, smoke and/or vapors.</i>
Hazards from the Product	<i>Contents extremely flammable. In a fire or if heated, a pressure increase will occur which may result in the container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.</i>
Mechanical Impact Sensitivity	<i>Probably not sensitive as material is stable.</i>
Static Discharge Sensitivity	<i>Vapors within the flammable limits may be ignited by a static discharge of sufficient energy.</i>

Special Protection Actions for Fire-Fighters

Protective Actions	<i>Use water spray to cool fire exposed containers, as contents may rupture from heat developed pressure.</i>
---------------------------	---

SAFETY DATA SHEET

24-hr Emergency Phone Number
800-255-3924 (Chem-Tel)

Protective Equipment Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel No action shall be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.

For Emergency Responders Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

Environmental Precautions

Precautions Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods and Materials for Containment and Cleaning up

Containment Procedures Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.

Cleanup Procedures Avoid breathing vapors and ventilate the area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.

Other Information The North American Emergency Response Guidebook, the Australian Dangerous Goods-Initial Emergency Response Guide (SAA/SNZ HB 76), or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.

Prohibited Materials Combustible absorbent material such as sawdust, use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling

General Handling Precautions KEEP OUT OF THE REACH OF CHILDREN.

Hygiene Recommendations Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

Conditions for Safe Storage Including And Incompatibilities

Storage Requirements In the United States, storage of flammable materials should conform to NFPA 30 Flammable and Combustible Liquid. Outside the United States performance to local and/or federal codes should be observed. Keep containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition.

Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Incompatibilities Segregate storage away from materials indicated in Section 10.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

Occupational Exposure Limits

ID	AUSTRALIA TWA	ALBERTA OEL	CANADA		QUEBEC TWA	GERMANY MAK	JAPAN OEL	MEXICO MPEL-PTA	UNITED KINGDOM WEL	OSHA PEL	UNITED STATES		ACGIH TLV
			BC TWA	ONTARIO TWAEV							NIOSH REL	NIOSH IDLH	
1	400 ppm	400 ppm	200 ppm	200 ppm	400 ppm	500 mg/m ³	400 ppm	400 ppm	200 ppm	400 ppm	400 ppm	2000 ppm	200 ppm
2	200 ppm	200 ppm	200 ppm	200 ppm	200 ppm	270 mg/m ³	200 ppm	200 ppm	200 ppm	200 ppm	200 ppm	6000 ppm	200 ppm

Biological Exposure Indices

ID	DETERMINANT	SAMPLING TIME	BEI	NOTATION
1	Acetone in urine	End of shift at end of workweek	40 mg/L	Ns, B
2	Methanol in urine	End of shift	15 mg/L	Ns, B

Appropriate Engineering Controls

Engineering Measures Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

Individual Protection Measures

Hygiene Considerations Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. Keep out the reach of children. Wash hands after use.

Thermal Hazards This product does not present a thermal hazard.

SAFETY DATA SHEET

24-hr Emergency Phone Number
800-255-3924 (Chem-Tel)

Respiratory Protection	<i>An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.</i>
Skin Protection	<i>For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.</i>
Eye/Face Protection	<i>Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.</i>
Other Protective Equipment	<i>Safety showers and eye-wash stations should be available in the workplace near where the material will be used.</i>

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	<i>> 64.6 °C (148.2 °F)</i>	Melting / Freezing Point	<i>> -97.7 °C (-143.8 °F)</i>
Flash Point	<i>> 11.0 °C (51.8 °F)</i>	Decomposition Temperature	<i>Not Available</i>
Explosive Limits	<i>2.00% - 36.00%</i>	Autoignition Temperature	<i>385.0 °C (727.0 °F)</i>
Flammability	<i>Class IB Liquid</i>	Relative Density (H2O = 1)	<i>0.782 g/cc</i>
Molecular Weight	<i>Not Available</i>	Weight	<i>6.524 lbs/gal</i>
Vapor Pressure	<i>52.730 mm Hg</i>	pH	<i>Not Available</i>
Vapor Density	<i>2.070 g/cc Maximum</i>	Evaporation Rate (nBac = 1)	<i>> 2.1</i>
Physical State	<i>Liquid</i>	Partition Coefficient	<i>Not Available</i>
Viscosity	<i>Not Available</i>	Refractive Index	<i>Not Available</i>
Odor / Odor Threshold	<i>Alcohol</i>	Heat of Combustion	<i>12,874.323 BTU/lb</i>
Appearance / Color	<i>Clear</i>	Water Solubility	<i>Not Available</i>
Percent Volatile	<i>100% Wt (100% Vol) Max</i>	VOC Content	<i>6.524 lbs/gal (781.785 g/L)</i>
Percent VOC	<i>100% Wt (100% Vol) Max</i>	HAP Content	<i>0.329 lbs/gal (39.36 g/L)</i>
Solids/Non Volatile Content	<i>None</i>	Maximum Incremental Reactivity	<i>0.710 g O3/g</i>

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	<i>No specific test data related to reactivity is available for this product or its ingredients.</i>
Chemical Stability	<i>This product is stable.</i>
Hazardous Reactions	<i>Under normal conditions of storage and use, hazardous reactions are not expected to occur.</i>
Conditions to Avoid	<i>Keep away from heat, sparks, flame, and red hot metal.</i>
Material Incompatibility	<i>Acetaldehyde, Alkali Metals, Aluminum, Carbon Tetrachloride, Chlorine, Diethyl Zinc, Ethylene Oxide, Hydrogen Peroxide, Isocyanates, Mineral Acids, Perchloric and Permonosulfuric Acids, Strong Acids, Strong Oxidizing Agents, Trinitromethane</i>
Decomposition Products	<i>Oxides of carbon.</i>

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity

ID	ORAL LD50		DERMAL LD50		INHALATION LC50		
	VALUE	SPECIES	VALUE	SPECIES	VALUE	TIME	SPECIES
1	4720 mg/kg	rat	12890 mg/kg	rabbit	17000 ppm	4h	rat
2	5850 mg/kg	rat	15800 mg/kg	rabbit	64000 ppm	4h	rat

Skin Corrosion/Irritation	<i>None of the ingredients are known to be corrosive to the skin or cause skin irritation.</i>
Eye Damage/Irritation	<i>Isopropanol causes serious eye irritation.</i>
Respiratory Irritation	<i>None of the ingredients are known to cause respiratory irritation.</i>
Respiratory or Skin Sensitization	<i>None of the ingredients are known to cause sensitization.</i>
Germ Cell Mutagenicity	<i>None of the ingredients are known or suspected of causing genetic defects.</i>
Carcinogen Data	<i>None of the ingredients are known or suspected carcinogens.</i>
Reproductive Toxicity	<i>Methanol is known by the state of California to cause birth defects or other reproductive harm.</i>
STOT-Single Exposure	<i>Isopropanol may cause drowsiness or dizziness. Methanol causes damage to organs.</i>
STOT-Repeated Exposure	<i>None of the ingredients are known to cause specific target organ effects through prolonged or repeated exposure.</i>
Aspiration Hazard	<i>Methanol may be fatal if swallowed and enters airways.</i>

SAFETY DATA SHEET

24-hr Emergency Phone Number
800-255-3924 (Chem-Tel)

Information on the Likely Routes of Exposure

Routes of Exposure *Skin contact, absorption, eye contact, inhalation.*

Symptoms Related to the Physical, Chemical and Toxicological Characteristics

Symptoms of Exposure *Blindness, dermatitis, drowsiness, dry cracking skin, eye irritation, skin irritation, throat irritation, upper respiratory system irritation, visual disturbance, vomiting.*

Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure

Delayed Effects *Ingestion of methanol may cause blindness.*

Immediate Effects *No known immediate effects.*

Chronic Effects *Not available.*

Medical Conditions Aggravated *May aggravate personnel with pre-existing disorders associated with any of the Target Organs.*

Target Organs *Cardiovascular system, central nervous system, eye, respiratory system, skin.*

Interactive Effects

Synergistic Effects *No known synergistic effects.*

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity

ID	TYPE	FISH			INVERTEBRATES			AQUATIC PLANTS			MICROORGANISMS		
		VALUE	PERIOD	TYPE	VALUE	PERIOD	TYPE	VALUE	PERIOD	TYPE	VALUE	PERIOD	
1	LC50	9460 mg/L	96h	EC50	> 10000 mg/L	24h	EC50	> 1000 mg/L	72h	LOEC	4930 mg/L	72h	
2	LC50	15400 mg/L	96h	EC50	> 10000 mg/L	48h	EC50	22000 mg/L	96h	EC5	6600 mg/L	16h	

Ecological Data

ID	PERSISTENCE	PERSISTENCE AND DEGRADABILITY			BIOACCUMULATIVE POTENTIAL		MOBILITY
		BOD	COD	ThOD	Pow / Kow	BCF	
1				2400 mg/g	0.05 log Kow	3.162 log BCF	0.122 log Koc
2		850 mg/g	1500 mg/g	1500 mg/g	-77.0 log Pow	0.48 log BCF	0.44 log Koc

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal *Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.*

Waste Disposal of Packaging *Consult with your local landfill to determine if empty small containers can be disposed of with regular trash. For disposal of large containers (typically 10 gallon or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.*

Landfill Precautions *Not Available*

Incineration Precautions *Not Available*

SECTION 14 - TRANSPORTATION INFORMATION

	DOT	ICAO/IATA	IMDG	ADR	TDG
ID Number	UN1993	UN1993	UN1993	UN1993	UN1993
Proper Shipping Name	Flammable Liquid, NOS (Contains Isopropanol and Methanol), Limited Quantity	Flammable Liquid, NOS (Contains Isopropanol and Methanol), Limited Quantity	Flammable Liquid, NOS (Contains Isopropanol and Methanol), Limited Quantity	Flammable Liquid, NOS (Contains Isopropanol and Methanol), Limited Quantity	Flammable Liquid, NOS (Contains Isopropanol and Methanol), Limited Quantity
Hazard Class(es)	3	3	3	3	3
Packing Group	II	II	II	II	II
Environmental Hazards	No	No	No	No	No
Special Precautions	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

SAFETY DATA SHEET

24-hr Emergency Phone Number
800-255-3924 (Chem-Tel)

Hazard Labels					
---------------	--	--	--	--	--

SECTION 15 - REGULATORY INFORMATION

United States - Federal Regulations

ID	TSCA LISTED	SARA 302 EHS TPQ	RCRA	CERCLA	SARA 313	FIRE	REACTIVITY	SARA 311/312 ACUTE	CHRONIC	PRESSURE	CLEAN AIR ACT HAP	CLEAN AIR ACT SOCM1	CLEAN WATER ACT
1	✓					Yes		Yes					
2	✓		U154	5,000	5 %	Yes		Yes			Yes	Yes	

United States - State Regulations

ID	CA P-65	DE RQ	MA RTK CODES	ME TYPE	ME RQ	RTK	MN AIR	WATER	NJ RTK	AIR	NY LAND	ACUTE	PA LISTED	WA PEL TWA	WI TABLE	WV TAP
1			2,4,5,6 F9		20000	ANO			Yes				Yes-E	400 ppm		
2	D	5,000	2,4,5,6 F8 F9		2000	ANO	Yes		Yes	5000	1		Yes-E	200 ppm		

Canadian Regulations

ID	WHMIS CATEGORIES										CHEMICAL LISTS		
	A	B	C	D1A	D1B	D2A	D2B	D3	E	DSL	NDSL	NPRI	
1		B2					✓				✓		1A,5
2		B2			✓	✓	✓				✓		1A,5

CPR Notice

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Classification

B2,D1B,D2A,D2B

WHMIS Symbols



European Union Regulations

ID	1907/2006 SVHC	67/548/EEC CLASSIFICATION	HAZARD CODES	1272/2008 PICTOGRAM CODES	SUPPL. CODES
	1		F; Xi	H225,H319,H336	GHS02,GHS07,Drg
2		F; T	H225,H331,H311,H301,H370**	GHS02,GHS06,GHS08,Dgr	

Classification According to EU Directive 1999/45/EC or 67/548/ECC (see Section 16 for full text)

67/548/EEC Pictograms



Risk Phrases

11-30/23/24/25-36-67

Safety Phrases

2-16-24/25-26-36/37-45

International Regulations

Chemical Weapons Convention

None of the ingredients are listed on the convention's schedules.

SECTION 16 - OTHER INFORMATION

Full Text of EU Phrases and Precautionary Statements

CODE	HAZARD STATEMENTS
H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled

SAFETY DATA SHEET

24-hr Emergency Phone Number

800-255-3924 (Chem-Tel)

CODE	SUPPLEMENTAL STATEMENTS
None	

CODE	PRECAUTIONARY STATEMENTS
P102	Keep out of reach of children
P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion proof equipment
P242	Use only non-sparking tools
P243	Take precautions against static discharge
P260	Do not breath fumes
P264	Wash hands thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/protective clothing/eye protection/face protection
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

CODE	RISK PHRASES
11	Highly flammable
39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed
36	Irritating to eyes
67	Vapours may cause drowsiness and dizziness

CODE	SAFETY PHRASES
2	Keep away from children
16	Keep away from sources of ignition – no spoking
24/25	Avoid contact with skin and eyes
36/37	Wear suitable protective clothing and gloves
45	In case of accident, or if you feel unwell, seek medical advice immediately

SDS Revision History
Revision 1, 01/27/2010 - original
Revision 2, 06/26/2012 - updated to include GHS and CLP information
Revision 3, 06/10/2013 - updated to full GHS compliance

SDS Prepared By Hazard Communication Associates, sds@hazcom411.com

Disclaimer of Liability
The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

References and Sources
CAMEO Database of Hazardous Materials (<http://cameochemicals.noaa.gov>)
CHEMpendium Database (<http://ccinfoweb.ccohs.ca/chempendium/search.html>)
ChemSpider Chemical Database (<http://chemspider.com>)
European Chemical Substances Information System (<http://esis.jrc.ec.europa.eu>)
European Chemicals Agency (<http://echa.europa.eu>)
International Chemical Safety Cards (<http://www.cdc.gov/niosh/ipcs/ipccard.html>)
IUCRID Chemical Data Sheets Information System (<http://esis.jrc.ec.europa.eu/index.php?PGM=dat>)
Merck Chemical Database (<http://www.merckmillipore.co.uk/chemicals>)
NIOSH Pocket Guide to Chemical Hazards (<http://www.cdc.gov/niosh/npg/>)
Right to Know Hazardous Substance Fact Sheets (<http://web.doh.state.nj.us/rtkhsfs/indexfs.aspx>)
RTECS Database (<http://ccinfoweb.ccohs.ca/rtecs/search.html>)
SOLV-DB, Solvent Database (<http://solvdb.ncms.org/solvdb.htm>)
Toxic Substances Portal (<http://www.atsdr.cdc.gov/toxprofiles/index.asp>)
TOXNet (<http://toxnet.nlm.nih.gov>)

SAFETY DATA SHEET

24-hr Emergency Phone Number

800-255-3924 (Chem-Tel)

Abbreviations Used

ACGIH	American Conference of Industrial Hygienists	NDSL	Non-Domestic Substance List (Canada)
ADR	European Agreement ... International Carriage of Dangerous Goods by Road	NIOSH	National Institute for Occupational Safety and Health (USA)
BCF	Bioconcentration Factor	NJ	New Jersey
BEI	Biological Exposure Index	NOEC	No Observed Effect Concentration
BOD	Biochemical Oxygen Demand	NPRI	National Pollutant Release Inventory (Canada)
CA	California	NTP	National Toxicity Program (USA)
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act (USA)	NY	New York
CFR	Code of Federal Regulations (USA)	OEL	Occupational Exposure Limit
CLP	Classification, Labelling and Packaging of Substances (Europe)	OSHA	Occupational Safety and Health Administration (USA)
COD	Chemical Oxygen Demand	P-65	Proposition 65 (USA)
CPR	Controlled Products Regulations (Canada)	PA	Pennsylvania
DE	Delaware	Pow	Octanol-Water Partition Coefficient
DOT	Department of Transportation (USA)	ppm	Parts per Million
DSL	Domestic Substance List (Canada)	psig	Pounds per Square Inch Gage
EC	European Community	RCRA	Resource Conservation and Recovery Act (USA)
EC50	Effective Concentration 50%	REL	Recommended Exposure Limit
EHA	Extremely Hazardous Substance	RQ	Reportable Quantity
EPA	Environmental Protection Agency (USA)	RTK	Right to Know
g/cc	Grams per Cubic Centimeter	SARA	Superfund Amendments and Reauthorization Act (USA)
GHS	Globally Harmonized System	SDS	Safety Data Sheet
HAP	Hazardous Air Pollutant	SOCMI	Synthetic Organic Chemical Manufacturing Industry (USA)
IARC	International Agency for Research on Cancer	STOT-RE	Suspected Target Organ Toxin, Repeat Exposure
IATA	International Air Transportation Association	STOT-SE	Suspected Target Organ Toxin, Single Exposure
IC50	Half Maximal Inhibitory Concentration	SVHC	Substance of Very High Concern
ICAO	International Civil Aviation Organization	TAP	Toxic Air Pollutant
IDLH	Immediately Dangerous to Life and Health	TDG	Transportation of Dangerous Goods (Canada)
IMDG	International Maritime Dangerous Goods	ThOD	Theoretical Oxygen Demand
Kow	Octanol-Water Partition Coefficient	TLV	Threshold Limit Value
lbs/gal	Pounds per Gallon	TPQ	Threshold Planning Quantity
LC50	Lethal Concentration 50%	TSCA	Toxic Substances Control Act (USA)
LD50	Lethal Dosage 50%	TWA	Time Weighted Average
MA	Massachusetts	TWAEV	Time Weighted Average Exposure Value
MAK	Maximale Arbeitsplatz Konzentration (Maximum Workplace Concentration)	VOC	Volatile Organic Compound
Max	Maximum	WA	Washington
mg/L	Milligrams per Litre	WEL	Workplace Exposure Limit
mg/m ³	Milligrams per Cubic Meter	WHMIS	Workplace Hazardous Materials Information System (Canada)
MN	Minnesota	WI	Wisconsin
MPEL-PTA	Maximum Permissible Exposure Limit on Pondered Time Average	WV	West Virginia