Part No. See 1.1 (Liquid)

Print Date: 14/11/2022 Revision Date: 11/14/2022 Supersedes Date: 10/19/2018 Issue Date: 8/13/2015

Version: 9.0 (EN)-US Page: 1/9

Gun Medic Lube

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1 - IDENTIFICATION

Product Identifier 1.1

Product Name : Gun Medic Lube **Manufacturer Product Number** : P7503CT & P7504CT

: P7502CT GM4 Pillow Pack - Inactive Other Manufacturer Ids **Supplier Product Numbers** : GM4WPDQ - 2 fl. oz/25 pk & GM4 - 2 fl. oz

1.2 Other Means of Identification

Other Identifiers : Not Available

1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Gun Lubricant **Restrictions on Use** : None Identified

1.4 **Supplier Details**

	Manufacturer Details	Supplier Details
Company Name :		Bushnell Holdings Inc.
Address :		22101 West 167th St., Olathe, KS 66062 - United
		States
Phone Number :		1-800-423-3537
Fax Number :		
Email :		dangerous.goods@vistaoutdoor.com
Website :		

1.5 24 hr Emergency Phone Number

: Emergency Telephone Number (Hazardous Material/Dangerous Goods Transportation Emergency ONLY) **Emergency Number**

Emergency number: 1-800-424-9300 (Inside US), 01-703-527-3887 (Outside US) - (CHEMTREC, Day or

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture			
Flam. Liq. 2	H225	Physical Hazards	Flammable liquids Category 2
Eye Irrit. 2a	H319	Health Hazards	Serious eye damage/eye irritation Category 2A
Stot Se 1	H370	Health Hazards	Specific target organ toxicity (single exposure) Category 1
Aquatic Acute 3	H402	Environmental Hazards	Hazardous to the aquatic environment – Acute Hazard Category 3
Aquatic Chronic 3	H412	Environmental Hazards	Hazardous to the aquatic environment – Chronic Hazard Category 3

Label Elements 2.2

Hazard Pictograms







Signal Word Danger

: Highly flammable liquid and vapor **Hazard Statements** H225

H319 : Causes serious eye irritation H370 : Causes damage to organs H402 : Harmful to aquatic life

H412 : Harmful to aquatic life with long lasting effects

Part No. See 1.1 (Liquid)

Print Date: 14/11/2022 Revision Date: 11/14/2022 Supersedes Date: 10/19/2018 Issue Date: 8/13/2015

Version: 9.0 (EN)-US Page: 2/9

Gun Medic Lube

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	Precautionary Statements	P210	: Keep away from heat, hot surfaces, sparks, open flames and other ignition source
--	--------------------------	------	--

No smokina.

P233 : Keep container tightly closed.

P240 : Ground/Bond container and receiving equipment.

P241 : Use explosion-proof electrical/ventilating/lighting equipment.

P242 : Use only non-sparking tools.

: Take precautionary measures against static discharge. P243

P260 Do not breathe spray.

P264 : Wash hands thoroughly after handling.

P270 : Do not eat, drink or smoke when using this product.

P273 : Avoid release to the environment. P280 : Wear protective gloves and eye protection.

P303+P361+P353 : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P307+P311 : If exposed: Call a poison center/doctor.

P337+P313 : If eye irritation persists: Get medical advice/attention.

P370+P378 : In case of fire: Use water, CO2, dry chemical, or universal aqueous film forming foam

to extinguish.

P403+P235 : Store in a well-ventilated place. Keep cool.

P405 : Store locked up.

P501 : Dispose of contents/container to local regulations.

Other Hazards Which Do Not Result In Classification 2.3

Hazards Not Otherwise Classified : None Identified.

Unknown acute toxicity

44.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

44.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

44.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (vapors))

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance / Mixture

Substance / Mixture : Mixture

3.2 Composition

Substance name	CAS Number	% wt*	Classification
Ethanol	64-17-5	30 – 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
Methanol	67-56-1	1-5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 1, H370
Ethyl Acetate	141-78-6	1-5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 - FIRST-AID MEASURES

Description of First-Aid Measures 4.1

General Measures : If exposed or concerned: Get medical advice/attention.

Inhalation : Remove person to fresh air and keep comfortable for breathing.

Part No. See 1.1 (Liquid)

Print Date: 14/11/2022 Revision Date: 11/14/2022 Supersedes Date: 10/19/2018 Issue Date: 8/13/2015

Version: 9.0 (EN)-US Page: 3/9

Gun Medic Lube

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin Contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.

: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue **Eye Contact**

rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion : Call a poison center or a doctor if you feel unwell.

First-Aid Responder Protection : Wear adequate personal protective equipment based on the nature and severity of the emergency.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure : Eye Irritation, Nose Irritation, Throat Irritation, Dermatitis, Skin Irritation, Headache, Dizziness, Nausea,

Narcosis, Upper Respiratory Tract Irritation, Drowsiness, Vomiting, Optical Nerve Damage.

Delayed Effects : No known delayed effects. **Immediate Effects** : No known immediate effects.

Chronic Effects : Methyl alcohol may be fatal or cause blindness if swallowed.

Target Organs : Central Nervous System, Eyes, Gastrointestinal Tract, Respiratory System, Skin.

4.3 **Indication of Immediate Medical Attention and Special Treatment**

Notes to Physician : Treat symptomatically. Specific Treatments/Antidotes : No Information Available.

Medical Conditions Aggravated : May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

SECTION 5 - FIRE-FIGHTING MEASURES

Suitable Extinguishing Media 5.1

Extinguishing Media : Water, carbon dioxide, dry chemical, universal aqueous film forming foam.

Unsuitable Media : Water iet.

5.2 Specific Hazards Arising from the Chemical or Mixture

Hazardous Combustion Products : Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.

Specific Hazards During Firefighting : CONTENTS HIGHLY FLAMMABLE. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

5.3 **Special Protective Actions for Fire-Fighters**

Firefighting Instructions : Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed

pressure.

Protection during Firefighting : Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 **Personal Precautions, Protective Equipment and Emergency Procedures**

For Non-Emergency Personnel : No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove

ignition sources and provide adequate ventilation only if it is safe to do so.

: Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency **For Emergency Personnel**

personnel above.

Environmental Precautions 6.2

Environmental Precautions : Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental

contamination.

6.3 Methods and Materials for Containment and Cleaning up

Containment Procedures : Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.

Cleanup Procedures : Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and

place in safety containers for proper disposal.

Other Information : The North American Emergency Response Guidebook or similar resources providing emergency response

information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.

Part No. See 1.1 (Liquid)

Print Date: 14/11/2022 Revision Date: 11/14/2022 Supersedes Date: 10/19/2018 Issue Date: 8/13/2015

Version: 9.0 (EN)-US Page: 4/9

Gun Medic Lube

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7 - HANDLING AND STORAGE

7.1 **Precautions for Safe Handling**

General Handling Precautions

: KEEP OUT OF THE REACH OF CHILDREN. When using in spray application, conformance to NFPA 33 Spray

: Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

Application using Flammable and Combustible Materials is recommended.

Hygiene Recommendations

Prohibited Materials

: Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

7.2 **Conditions for Safe Storage Including Any Incompatibilities**

Storage Requirements

: Storage of individual cans should be done in an area below 55°C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended.

Incompatibilities NFPA 30B Classification : Segregate storage away from materials indicated in Section 10. : This product is classified as a Level 3 Aerosol per NFPA 30B

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 **Control Parameters**

Ethanol (64-17-5)		
ACGIH	ACGIH OEL Ceiling	1000 ppm
OSHA	OSHA PEL (TWA) [1]	1900 mg/m³
OSHA	OSHA PEL (TWA) [2]	1000 ppm
NIOSH	IDLH [ppm]	3300 ppm
NIOSH	NIOSH REL (TWA)	1900
NIOSH	NIOSH REL TWA [ppm]	1000 ppm
California	California PEL (TWA) (mg/m3)	1900 mg/m³
California	California PEL (TWA) (ppm)	1000 ppm

Methanol (67-56-1)		
ACGIH	ACGIH OEL TWA	200 ppm
ACGIH	ACGIH OEL Ceiling	250 ppm
OSHA	OSHA PEL (TWA) [1]	260 mg/m³
OSHA	OSHA PEL (TWA) [2]	200 ppm
NIOSH	IDLH [ppm]	6000 ppm
NIOSH	NIOSH REL TWA [ppm]	200 ppm
California	California PEL (TWA) (mg/m3)	260 mg/m³
California	California California PEL (TWA) (ppm) 200 ppm	
California California PEL (STEL) (mg/m3) 325 mg/m³		325 mg/m³
California	California PEL (STEL) (ppm)	250 ppm
California	California PEL (Ceiling) (ppm)	1000 ppm
Biological Exposure Index	xposure Index Methanol in Urine, End of shift (B,Ns) 15 mg/l	

Ethyl Acetate (141-78-6)	Ethyl Acetate (141-78-6)		
ACGIH	ACGIH OEL TWA	400 ppm	
OSHA	OSHA PEL (TWA) [1]	1400 mg/m³	
OSHA	OSHA PEL (TWA) [2]	400 ppm	
NIOSH	IDLH [ppm]	2000 ppm	
NIOSH	NIOSH REL TWA [ppm]	400 ppm	
California	California PEL (TWA) (mg/m3)	1400 mg/m³	
California	California PEL (TWA) (ppm)	400 ppm	

8.2 **Exposure Controls**

Engineering Measures

: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

Personal Protective Equipment

Part No. See 1.1 (Liquid)

Print Date: 14/11/2022 Revision Date: 11/14/2022 Supersedes Date: 10/19/2018 Issue Date: 8/13/2015

Version: 9.0 (EN)-US Page: 5/9

Gun Medic Lube

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye / Face Protection : Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

: Chemical-resistant gloves, tested according to ASTM F903 - 17.

: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the

hazardous substance and specific to the place of work.

Skin and Body Protection : For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged

or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

Respiratory Protection : An approved respirator may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. Under those circumstances, users should be provided with either a half-facepiece (if wearing safety glasses) or a full-facepiece (if not wearing safety glasses) air-

purifying respirator, fitted with organic vapor cartidges and P95 filters.

Filter type : Organic vapour type.

Compliance : If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.

Other Protective Equipment Safety showers and eye-wash stations should be available in the workplace near where the material will be

Environmental Exposure Controls : Avoid release to the environment.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties			
Boiling Point	> 78.00 °C	Melting / Freezing Point	>-114.15
Flash Point, Liquid	> 14.00 °C		
Explosive Limits	LEL: 1.00 UEL: 19.00 vol % (v/v%)	Autoignition Temperature, Liquid	> 320.00 °C
Flammability	Highly Flammable Liquid	Density	0.891 g/cm³
Molecular Weight	Not Available	Weight	7.436 lbs/gal
Vapor Pressure	Not Available	рН	Not Available
Vapor Density	Not Available	Evaporation Rate (nBAc=1)	Not Available
Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Pressurized Product	Heat Of Combustion	Not Available
Appearance / Color	Amber	Water Solubility	Not Available
Odor	Characteristic	Decomposition Temperature	Not Available

9.2 Environmental Properties			
Percent Volatile	54.00 % wt	VOC Regulatory	481.20 g/L (4.02 lbs/gal)
Percent VOC	54.00 % wt	VOC Actual	481.20 g/L (4.02 lbs/gal)
Percent HAP	2.16 % wt	HAP Content	19.25 g/L (0.16 lbs/gal)
Global Warming Potential	0.06 GWP	Maximum Incremental Reactivity	0.8688 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Hand Protection

Remarks

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

10.2 **Chemical Stability**

Chemical Stability : This product is stable.

10.3 **Possibility of Hazardous Reactions**

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 **Conditions to Avoid**

Conditions to Avoid : Electrostatic Discharge, Other Ignition Sources, Flames, Sparks.

Part No. See 1.1 (Liquid)

Print Date: 14/11/2022 Revision Date: 11/14/2022 Supersedes Date: 10/19/2018 Issue Date: 8/13/2015

Version: 9.0 (EN)-US Page: 6/9

Gun Medic Lube

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5 **Incompatible Materials**

Materials to Avoid : Strong Oxidizing Agents, Alkali Metals, Strong Acids, Potassium t-Butoxide, Hydrogen Peroxide.

10.6 **Hazardous Decomposition Products**

Thermal Decomposition : Oxides of carbon, Formaldehyde.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 **Information on Toxicological Effects**

Ethanol (CAS: 64-17-5 / EC: 200-578-6)	
LD50 Oral (Rat)	10740 mg/kg (MERCK)
LD50 Dermal (Rabbit)	> 15800 mg/kg (ChemInfo)
LC50 Inhalation (Rat)	124.7 mg/l/4h (MERCK)
LC50 Inhalation (Rat)	32380 ppm/4h (ChemInfo)

Methanol (CAS: 67-56-1 / EC: 200-659-6)		
LD50 Oral (Rat) 5850 mg/s		5850 mg/kg (ChemInfo)
	LD50 Dermal (Rabbit)	15800 mg/kg (RTECS)
	LC50 Inhalation (Rat)	131.25 mg/l/4h (ECHA)
	LC50 Inhalation (Rat)	64000 ppm/4h (ChemInfo)

Ethyl Acetate (CAS: 141-78-6 / EC: 205-500-4)	
LD50 Oral (Rat)	5620 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 18000 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat) 10600 ppm/4h (ChemInfo)	

Routes Of Exposure : Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.

Delayed and Immediate Effects and Also Chronic

Effects from Short and Long Term Exposure

: See Section 4.2

Skin Corrosion/Irritation : Not classified

: Causes serious eye irritation. Eye Damage/Irritation

Respiratory or Skin Sensitization : Not classified **Germ Cell Mutagenicity** : Not classified **Reproductive Toxicity** : Not classified

STOT-Single Exposure : Causes damage to organs.

STOT-Repeated Exposure : Not classified **Aspiration Hazard** : Not classified

Carcinogen Data : None of the ingredients in the product are listed with OSHA, IARC, NTP or ACGIH as being a suspected or

known carcinogen in a concentration greater than 0.1% by weight.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 **Ecotoxicity and Ecological Properties**

Ethanol (64-17-5)		
LC50 Fish	14200 mg/l Fathead Minnow - 96h	
EC50 Daphnia	9268 – 14221 mg/l Water Flea - 48hr	
Persistence and Degradibility	Biodegradability 94% / 28 days.	
Biochemical Oxygen Demand	0.8 – 0.967 g O ₂ /g substance	
Chemical Oxygen Demand	1.7 g O₂/g substance	
Theoretical Oxygen Demand	$2.1 \text{ g } O_2/\text{g substance}$	
Log Pow	-0.35 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 24 °C)	
Bioacculative Potential	Low potential for bioaccumulation (Log Kow < 4).	

Methanol (67-56-1)	
LC50 Fish	15400 mg/l Bluegill Sunfish - 96h

Part No. See 1.1 (Liquid)

Print Date: 14/11/2022 Revision Date: 11/14/2022 Supersedes Date: 10/19/2018 Issue Date: 8/13/2015 Version: 9.0 (EN)-US

Page: 7/9

Gun Medic Lube

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
EC50 Daphnia	> 10000 mg/l Water Flea - 48hr	
EC50 Other Aquatic Organisms	22000 mg/l Freshwater Algae - 96hr	
Persistence and Degradibility	Biodegradability 72% / 5 days.	
Biochemical Oxygen Demand	$0.6 - 1.12$ g O_2/g substance	
Chemical Oxygen Demand	1.42 g O₂/g substance	
Theoretical Oxygen Demand	1.5 g O ₂ /g substance	
BCF Fish	< 10 (BCF; 72 h; Leuciscus idus)	
Log Pow	-0.77 (Experimental value; Other)	
Bioacculative Potential	Low potential for bioaccumulation (BCF < 500).	
Log Koc	0.44	

Ethyl Acetate (141-78-6)		
LC50 Fish	450 – 600 mg/l Rainbow Trout - 96hr	
LC50 Fish	220 – 250 mg/l Fathead Minnow - 96h	
LC50 Other Aquatic Organisms	560 mg/l Water Flea - 48hr	
EC50 Daphnia	2300 – 3090 mg/l Water Flea - 24hr	
EC50 Other Aquatic Organisms	4300 mg/l Green Algae - 24hr	
Persistence and Degradibility	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.	
Biochemical Oxygen Demand	0.293 g O₂/g substance	
Chemical Oxygen Demand	1.69 g O₂/g substance	
Theoretical Oxygen Demand	1.82 g O ₂ /g substance	
Biodegration	100 % 28 Days	
BCF Fish	30	
Log Pow	0.73	
Bioacculative Potential	Low potential for bioaccumulation (BCF < 500).	
Log Koc	0.778	

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 **Waste Treatment Methods**

Waste Disposal

: Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the $responsibility\ of\ the\ user\ to\ determine\ the\ proper\ storage,\ transportation,\ treatment,\ and/or\ disposal$ methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

Waste Disposal Of Packaging

: Consult with your local landfill to determine if empty small containers can be disposed of along with regular trash pickup. For disposal of large containers (typically 10 gallons or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.

: Not Available.

Landfill Precautions Incineration Precautions : Not Available.

SECTION 14 - TRANSPORTATION INFORMATION

14.1	UN Number		DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Number		:	UN1993	UN1993	UN1993
14.2	UN Proper Shipping Name		DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Proper Shipping Name		:	Flammable Liquid, NOS(Contains Ehtanol, Ethyl Acetate & Methanol), Limited Quantity	Flammable Liquid, NOS(Contains Ehtanol, Ethyl Acetate & Methanol), Limited Quantity	Flammable Liquid, NOS(Contains Ehtanol, Ethyl Acetate & Methanol), Limited Quantity
14.3	Transport Hazard Class(es)		DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Transpo	rt Hazard Class(es)	:	3	3	3
Labels		:	None	3 - Flammable liquid	None

Part No. See 1.1 (Liquid)

Print Date: 14/11/2022 Revision Date: 11/14/2022 Supersedes Date: 10/19/2018 Issue Date: 8/13/2015 Version: 9.0 (FN)-I/S

Version: 9.0 (EN)-US Page: 8/9

Gun Medic Lube

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



Limited Quantity



Y



EmS Code :

Not Applicable

Not Applicable

·

14.4 Packing Group

DOT (USA)

IATA (AIR)

IMDG (OCEAN)

Packing Group

:

:

None

14.5 Environmental Hazards

DOT (USA)

IATA (AIR)

IMDG (OCEAN)

Marine Pollutant

No

No

No

14.6 Special Precautions

Precautions

: None Identified

14.7 Transport in Bulk

Remarks

: Not applicable for product as supplied

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations

SARA Section 313

: Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methanol CAS-No. 67-56-1 1 – 5%

TSCA Section 12(b)

: This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D

CERCLA Reportable Quantity

: Chemical(s) subject to reporting requirements of Section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) if released to the environment at or above the reportable quantity

 Methanol
 CAS-No. 67-56-1
 5000 lb

 Ethyl Acetate
 CAS-No. 141-78-6
 5000 lb

15.2 State Regulations

California Proposition 65

: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Methanol (67-56-1) Developmental Toxicity Yes 2.16 %

State Right-to-Know Lists

: The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

Ethanol (64-17-5)	U.S New Jersey - Right to Know Hazardous Substance List
Methanol (67-56-1)	U.S New Jersey - Right to Know Hazardous Substance List
	U.S Pennsylvania - RTK (Right to Know) List
Ethyl Acetate (141-78-6)	U.S New Jersey - Right to Know Hazardous Substance List
	U.S Pennsylvania - RTK (Right to Know) List
Tricresyl Phosphate (1330-78-5)	U.S New Jersey - Right to Know Hazardous Substance List
Antimony Diamyldithiocarbamate (15890-25-2)	U.S New Jersey - Right to Know Hazardous Substance List
	U.S Pennsylvania - RTK (Right to Know) List

SECTION 16 - OTHER INFORMATION

Indication of changes : Section Changed item Change

Part No. See 1.1 (Liquid)

Print Date: 14/11/2022 Revision Date: 11/14/2022 Supersedes Date: 10/19/2018 Issue Date: 8/13/2015

Version: 9.0 (EN)-US Page: 9/9

Gun Medic Lube

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1	Supersedes	Modified
1	Revision date	Modified
1	Other Manufacturer IDs	Added
1	Supplier Product Numbers	Modified
1	Product code	Modified
9	Density	Modified
9	Relative vapor density at 20 °C	Added
9	Explosive limits (vol %)	Modified
9	Flash point	Modified
9	Boiling point	Modified
9	Auto-ignition temperature	Modified

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.