

SAFETY DATA SHEET

Part No. P7661CT & P7662CT
(Liquid)

Print Date: 17/11/2022
Revision Date: 11/17/2022
Supersedes Date: 12/5/2018
Issue Date: 10/28/2016
Version: 3.0 (EN)-US
Page: 1/8

Hoppe's Black Lubricant

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : Hoppe's Black Lubricant
Manufacturer Product Number : P7661CT & P7662CT
Supplier Product Numbers : HBL4 - 4 oz. & HBL2 - 2 oz.

1.2 Other Means of Identification

Other Identifiers : Not Available

1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Lubricating oil for firearms
Restrictions on Use : None Identified

1.4 Supplier Details

	Manufacturer Details	Supplier Details
Company Name		Bushnell Holdings Inc.
Address		22101 West 167th St., Olathe, KS 66062 - United States
Phone Number		1-800-423-3537
Fax Number		
Email		dangerous.goods@vistaoutdoor.com
Website		

1.5 24 hr Emergency Phone Number

Emergency Number : Emergency Telephone Number (Hazardous Material/Dangerous Goods Transportation Emergency ONLY)
Emergency number: 1-800-424-9300 (Inside US), 01-703-527-3887 (Outside US) - (CHEMTREC, Day or Night)

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Flam. Liq. 2	H225	Physical Hazards	Flammable liquids Category 2
Eye Irrit. 2a	H319	Health Hazards	Serious eye damage/eye irritation Category 2A
Skin Sens. 1	H317	Health Hazards	Skin sensitization, Category 1
Aquatic Acute 3	H402	Environmental Hazards	Hazardous to the aquatic environment – Acute Hazard Category 3

2.2 Label Elements

Hazard Pictograms



GHS02



GHS07

Signal Word

Danger

Hazard Statements

H225 : Highly flammable liquid and vapor
H317 : May cause an allergic skin reaction
H319 : Causes serious eye irritation
H402 : Harmful to aquatic life

Precautionary Statements

P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 : Keep container tightly closed.

SAFETY DATA SHEET

Part No. P7661CT & P7662CT
(Liquid)

Print Date: 17/11/2022
Revision Date: 11/17/2022
Supersedes Date: 12/5/2018
Issue Date: 10/28/2016
Version: 3.0 (EN)-US
Page: 2/8

Hoppe's Black Lubricant

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- P240 : Ground/Bond container and receiving equipment.
P241 : Use explosion-proof electrical/ventilating/lighting equipment.
P242 : Use only non-sparking tools.
P243 : Take precautionary measures against static discharge.
P261 : Avoid breathing fumes, spray.
P264 : Wash hands thoroughly after handling.
P272 : Contaminated work clothing must not be allowed out of the workplace.
P273 : Avoid release to the environment.
P280 : Wear protective gloves and eye protection.
P303+P361+P353 : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 : If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 : If eye irritation persists: Get medical advice/attention.
P363 : Wash contaminated clothing before reuse.
P370+P378 : In case of fire: Use water, CO₂, dry chemical, or universal aqueous film forming foam to extinguish.
P403+P235 : Store in a well-ventilated place. Keep cool.
P501 : Dispose of contents/container to applicable regulations.

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

2.4 Unknown acute toxicity

This product does not have any ingredients with an unknown acute toxicity.

43.28% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

43.28% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

43.28% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (vapors))

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance / Mixture

Substance / Mixture : Mixture

3.2 Composition

Substance name	CAS Number	% wt*	Classification
Ethanol	64-17-5	30 – 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
Calcium Bis(Dinonylnaphthalenesulphonate)	57855-77-3	0.1 – 1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400
Alkyl Dithiophosphate	Confidential	0.1 – 1	Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 - FIRST-AID MEASURES

4.1 Description of First-Aid Measures

- General Measures** : Call a poison center or a doctor if you feel unwell.
Inhalation : Remove person to fresh air and keep comfortable for breathing.
Skin Contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
Eye Contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SAFETY DATA SHEET

Part No. P7661CT & P7662CT
(Liquid)

Print Date: 17/11/2022
Revision Date: 11/17/2022
Supersedes Date: 12/5/2018
Issue Date: 10/28/2016
Version: 3.0 (EN)-US
Page: 3/8

Hoppe's Black Lubricant

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ingestion : Call a poison center or a doctor if you feel unwell.
First-Aid Responder Protection : Wear adequate personal protective equipment based on the nature and severity of the emergency.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure : Eye Irritation, Nose Irritation, Throat Irritation, Skin Irritation, Narcosis, Drowsiness.
Delayed Effects : No known delayed effects.
Immediate Effects : No known immediate effects.
Chronic Effects : No known chronic effects.
Target Organs : Central Nervous System, Eyes, Respiratory System, Skin.

4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician : Treat symptomatically.
Specific Treatments/Antidotes : No Information Available.
Medical Conditions Aggravated : May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media : Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media : Water jet.

5.2 Specific Hazards Arising from the Chemical or Mixture

Hazardous Combustion Products : Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
Specific Hazards During Firefighting : CONTENTS HIGHLY FLAMMABLE. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

5.3 Special Protective Actions for Fire-Fighters

Firefighting Instructions : Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed pressure.
Protection during Firefighting : Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel : No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Emergency Personnel : Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

6.2 Environmental Precautions

Environmental Precautions : Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

6.3 Methods and Materials for Containment and Cleaning up

Containment Procedures : Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.
Cleanup Procedures : Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
Other Information : The North American Emergency Response Guidebook or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.
Prohibited Materials : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

SAFETY DATA SHEET

Part No. P7661CT & P7662CT
(Liquid)

Print Date: 17/11/2022
Revision Date: 11/17/2022
Supersedes Date: 12/5/2018
Issue Date: 10/28/2016
Version: 3.0 (EN)-US
Page: 4/8

Hoppe's Black Lubricant

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling

- General Handling Precautions** : *KEEP OUT OF THE REACH OF CHILDREN. When using in spray application, conformance to NFPA 33 Spray Application using Flammable and Combustible Materials is recommended.*
- Hygiene Recommendations** : *Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.*

7.2 Conditions for Safe Storage Including Any Incompatibilities

- Storage Requirements** : *Storage of flammable materials should conform to NFPA 30 Flammable and Combustible Liquid. Keep containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition.*
- Incompatibilities** : *Segregate storage away from materials indicated in Section 10.*

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

Ethanol (64-17-5)

ACGIH	ACGIH OEL Ceiling	1000 ppm
OSHA	OSHA PEL (TWA) [1]	1900 mg/m ³
OSHA	OSHA PEL (TWA) [2]	1000 ppm
NIOSH	IDLH [ppm]	3300 ppm
NIOSH	NIOSH REL (TWA)	1900
NIOSH	NIOSH REL TWA [ppm]	1000 ppm
California	California PEL (TWA) (mg/m ³)	1900 mg/m ³
California	California PEL (TWA) (ppm)	1000 ppm

8.2 Exposure Controls

- Engineering Measures** : *Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.*
- Personal Protective Equipment**
- Eye / Face Protection** : *Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.*
- Hand Protection** : *Chemical-resistant gloves, tested according to ASTM F903-17.*
- Remarks** : *Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.*
- Skin and Body Protection** : *For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.*
- Respiratory Protection** : *Respiratory protection is not anticipated to be needed.*
- Compliance** : *If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.*
- Other Protective Equipment** : *Safety showers and eye-wash stations should be available in the workplace near where the material will be used.*
- Environmental Exposure Controls** : *Avoid release to the environment.*

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 78.00 °C	Melting / Freezing Point	> -114.15 °C
Flash Point, Liquid	> 14.00 °C		
Explosive Limits	LEL: 3.30 UEL: 19.00 vol % (v/v%)	Autoignition Temperature, Liquid	> 260.00 °C
Flammability	Highly Flammable Liquid	Density	0.891 g/cm ³
Molecular Weight	Not Available	Weight	7.434 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBac=1)	Not Available

SAFETY DATA SHEET

Part No. P7661CT & P7662CT
(Liquid)

Print Date: 17/11/2022
Revision Date: 11/17/2022
Supersedes Date: 12/5/2018
Issue Date: 10/28/2016
Version: 3.0 (EN)-US
Page: 5/8

Hoppe's Black Lubricant

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Liquid	Heat Of Combustion	Not Available
Appearance / Color	Black	Water Solubility	Not Available
Odor	Characteristic	Decomposition Temperature	Not Available

9.2 Environmental Properties

Percent Volatile	54.70 % wt	VOC Regulatory	487.26 g/L (4.07 lbs/gal)
Percent VOC	54.00 % wt	VOC Actual	481.02 g/L (4.01 lbs/gal)
Percent HAP	0.00 % wt	HAP Content	0.00 g/L (0.00 lbs/gal)
Global Warming Potential	0.00 GWP	Maximum Incremental Reactivity	0.9119 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

10.2 Chemical Stability

Chemical Stability : This product is stable.

10.3 Possibility of Hazardous Reactions

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 Conditions to Avoid

Conditions to Avoid : None Identified.

10.5 Incompatible Materials

Materials to Avoid : Strong Oxidizing Agents, Alkali Metals, Hydrogen Peroxide, Sulfuric Acid.

10.6 Hazardous Decomposition Products

Thermal Decomposition : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

Ethanol (CAS: 64-17-5 / EC: 200-578-6)

LD50 Oral (Rat)	10740 mg/kg (MERCK)
LD50 Dermal (Rabbit)	> 15800 mg/kg (ChemInfo)
LC50 Inhalation (Rat)	124.7 mg/l/4h (MERCK)
LC50 Inhalation (Rat)	32380 ppm/4h (ChemInfo)

Calcium Bis(Dinonylnaphthalenesulphonate) (CAS: 57855-77-3 / EC: 260-991-2)

LD50 Oral (Rat)	> 5000 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 20000 mg/kg (RTECS)
LC50 Inhalation (Rat)	> 18000 mg/m ³ (RTECS)

Alkyl Dithiophosphate (CAS: Confidential / EC:)

LD50 Oral (Rat)	11300 mg/kg (Lit.)
-----------------	--------------------

Routes Of Exposure : Eye Contact, Ingestion, Skin Contact, Inhalation.

Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure : See Section 4.2

Skin Corrosion/Irritation : Not classified

SAFETY DATA SHEET

Part No. P7661CT & P7662CT
(Liquid)

Print Date: 17/11/2022
Revision Date: 11/17/2022
Supersedes Date: 12/5/2018
Issue Date: 10/28/2016
Version: 3.0 (EN)-US
Page: 6/8

Hoppe's Black Lubricant

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye Damage/Irritation	: Causes serious eye irritation.
Respiratory or Skin Sensitization	: May cause an allergic skin reaction.
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Not classified
STOT-Single Exposure	: Not classified
STOT-Repeated Exposure	: Not classified
Aspiration Hazard	: Not classified
Carcinogen Data	: None of the ingredients in the product are listed with OSHA, IARC, NTP or ACGIH as being a suspected or known carcinogen in a concentration greater than 0.1% by weight.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity and Ecological Properties

Ethanol (64-17-5)

LC50 Fish	14200 mg/l Fathead Minnow - 96h
EC50 Daphnia	9268 – 14221 mg/l Water Flea - 48hr
Persistence and Degradability	Biodegradability 94% / 28 days.
Biochemical Oxygen Demand	0.8 – 0.967 g O ₂ /g substance
Chemical Oxygen Demand	1.7 g O ₂ /g substance
Theoretical Oxygen Demand	2.1 g O ₂ /g substance
Log Pow	-0.35 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 24 °C)
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).

Calcium bis(dinonylnaphthalenesulphonate) (57855-77-3)

LC50 Fish	0.28 mg/l 96hr
EC50 Daphnia	0.27 mg/l 48hr
BCF Fish	3.16
Log Pow	11.12
Log Kow	6.6

Alkyl Dithiophosphate (Confidential)

LC50 Fish	> 100 mg/l
EC50 Daphnia	> 100 mg/l
EC50 Other Aquatic Organisms	> 100 mg/l

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal	: Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
Waste Disposal Of Packaging	: Consult with your local landfill to determine if empty small containers can be disposed of along with regular trash pickup. For disposal of large containers (typically 10 gallons or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.
Landfill Precautions	: Not Available.
Incineration Precautions	: Not Available.

SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Number	: UN1993	UN1993	UN1993

SAFETY DATA SHEET




**Part No. P7661CT & P7662CT
(Liquid)**

Hoppe's Black Lubricant

Print Date: 17/11/2022
Revision Date: 11/17/2022
Supersedes Date: 12/5/2018
Issue Date: 10/28/2016
Version: 3.0 (EN)-US
Page: 7/8

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2 UN Proper Shipping Name	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Proper Shipping Name	: <i>Flammable Liquid, NOS (Contains Ethanol), Limited Quantity</i>	<i>Flammable Liquid, NOS (Contains Ethanol), Limited Quantity</i>	<i>Flammable Liquid, NOS (Contains Ethanol), Limited Quantity</i>

14.3 Transport Hazard Class(es)	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Transport Hazard Class(es)	: 3	3	3
Labels	: None	3 - Flammable liquid	None
Limited Quantity	: Yes 	Yes 	Yes 
EmS Code	: Not Applicable	Not Applicable	F-E, S-E

14.4 Packing Group	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Packing Group	: II	II	II

14.5 Environmental Hazards	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Marine Pollutant	: No	No	No

14.6 Special Precautions	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Precautions	: None Identified		

14.7 Transport in Bulk	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Remarks	: Not applicable for product as supplied		

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations	DOT (USA)	IATA (AIR)	IMDG (OCEAN)			
SARA Section 313	: Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.					
	<table border="1" style="width: 100%; border-collapse: collapse; font-size: x-small;"> <tr> <td style="width: 50%;">T-Butyl Alcohol</td> <td style="width: 25%;">CAS-No. 75-65-0</td> <td style="width: 25%;">0.01 – 0.1%</td> </tr> </table>	T-Butyl Alcohol	CAS-No. 75-65-0	0.01 – 0.1%		
T-Butyl Alcohol	CAS-No. 75-65-0	0.01 – 0.1%				
TSCA Section 12(b)	: This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D					
CERCLA Reportable Quantity	: This product or mixture is not known to contain a chemical or chemicals subject to the release reporting requirements of section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)					

15.2 State Regulations	DOT (USA)	IATA (AIR)	IMDG (OCEAN)				
California Proposition 65	: This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm						
State Right-to-Know Lists	: The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated						
	<table border="1" style="width: 100%; border-collapse: collapse; font-size: x-small;"> <tr> <td style="width: 50%;">Ethanol (64-17-5)</td> <td style="width: 50%;">U.S. - New Jersey - Right to Know Hazardous Substance List</td> </tr> <tr> <td>T-Butyl Alcohol (75-65-0)</td> <td>U.S. - New Jersey - Right to Know Hazardous Substance List</td> </tr> </table>	Ethanol (64-17-5)	U.S. - New Jersey - Right to Know Hazardous Substance List	T-Butyl Alcohol (75-65-0)	U.S. - New Jersey - Right to Know Hazardous Substance List		
Ethanol (64-17-5)	U.S. - New Jersey - Right to Know Hazardous Substance List						
T-Butyl Alcohol (75-65-0)	U.S. - New Jersey - Right to Know Hazardous Substance List						

SECTION 16 - OTHER INFORMATION

SAFETY DATA SHEET

Part No. P7661CT & P7662CT
(Liquid)

Hoppe's Black Lubricant

Print Date: 17/11/2022
Revision Date: 11/17/2022
Supersedes Date: 12/5/2018
Issue Date: 10/28/2016
Version: 3.0 (EN)-US
Page: 8/8

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Indication of changes

Section	Changed item	Change
1	Revision date	Modified
1	Supersedes	Modified
2.1	GHS-US classification	Modified
2.2	Hazard statements (GHS US)	Modified
2.2	Precautionary statements (GHS US)	Modified
3	Composition/Information on ingredients	Modified
6	For containment	Added
9	Boiling point	Modified
9	Flash point	Modified
9	Auto-ignition temperature	Added
9	Density	Modified
9	Relative vapor density at 20 °C	Added
9	Appearance	Added
9	Melting point	Modified
12.1	Ecology - general	Modified

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.