

SAFETY DATA SHEET

Part No. P5718CT (Aerosol)

Print Date: 11/11/2022
 Revision Date: 11/11/2022
 Supersedes Date: 10/25/2019
 Issue Date: 4/27/2006
 Version: 11.0 (EN)-US
 Page: 1/9

Hoppe's 9 Blast & Shine Firearm Action Grease Remover

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : Hoppe's 9 Blast & Shine Firearm Action Grease Remover
 Manufacturer Product Number : P5718CT
 Supplier Product Numbers : CD1

1.2 Other Means of Identification

Other Identifiers : Not Applicable

1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Solvent used on firearms.
 Restrictions on Use : None Identified

1.4 Supplier Details

	Manufacturer Details	Supplier Details
Company Name :		Bushnell Holdings Inc.
Address :		22101 West 167th St., Olathe, KS 66062 - United States
Phone Number :		1-800-423-3537
Fax Number :		
Email :		dangerous.goods@vistaoutdoor.com
Website :		

1.5 24 hr Emergency Phone Number

Emergency Number : Emergency Telephone Number (Hazardous Material/Dangerous Goods Transportation Emergency ONLY)
 Emergency number: 1-800-424-9300 (Inside US), 01-703-527-3887 (Outside US) - (CHEMTREC, Day or Night)

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Flam. Aerosol 2	H223	Physical Hazards	Flammable aerosol Category 2
Press. Gas (Comp.)	H280	Physical Hazards	Gases under pressure Compressed gas
Eye Irrit. 2a	H319	Health Hazards	Serious eye damage/eye irritation Category 2A
Stot Se 3	H336	Health Hazards	Specific target organ toxicity (single exposure) Category 3, Narcosis

2.2 Label Elements

Hazard Pictograms



GHS02



GHS04



GHS07

Signal Word

Warning

Hazard Statements

H223 : Flammable aerosol
 H280 : Contains gas under pressure; may explode if heated
 H319 : Causes serious eye irritation
 H336 : May cause drowsiness or dizziness

Precautionary Statements

P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 : Do not spray on an open flame or other ignition source.

SAFETY DATA SHEET

Part No. P5718CT (Aerosol)

Print Date: 11/11/2022
Revision Date: 11/11/2022
Supersedes Date: 10/25/2019
Issue Date: 4/27/2006
Version: 11.0 (EN)-US
Page: 2/9

Hoppe's 9 Blast & Shine Firearm Action Grease Remover

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- P251 : Pressurized container: Do not pierce or burn, even after use.
P261 : Avoid breathing spray.
P264 : Wash hands thoroughly after handling.
P271 : Use only outdoors or in a well-ventilated area.
P280 : Wear protective gloves and eye protection .
P304+P340 : If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 : Call physician if you feel unwell.
P337+P313 : If eye irritation persists: Get medical advice/attention.
P403 : Store in a well-ventilated place.
P410+P412 : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 : Dispose of contents/container to local regulations.

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

2.4 Unknown acute toxicity

- 3% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
3% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
3% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (vapors))

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance / Mixture

Substance / Mixture : Mixture

3.2 Composition

Substance name	CAS Number	% wt*	Classification
Acetone	67-64-1	≥ 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methyl Acetate	79-20-9	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methyl Ethyl Ketone	78-93-3	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Carbon Dioxide	124-38-9	1 – 5	Press. Gas (Comp.), H280

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 - FIRST-AID MEASURES

4.1 Description of First-Aid Measures

- General Measures** : Call a poison center or a doctor if you feel unwell.
- Inhalation** : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.
- Skin Contact** : Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing. . Wash skin with plenty of water.
- Eye Contact** : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Ingestion** : Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing. Call a poison center or a doctor if you feel unwell.
- First-Aid Responder Protection** : Wear adequate personal protective equipment based on the nature and severity of the emergency.

SAFETY DATA SHEET

Part No. P5718CT (Aerosol)

Hoppe's 9 Blast & Shine Firearm Action Grease Remover

Print Date: 11/11/2022
Revision Date: 11/11/2022
Supersedes Date: 10/25/2019
Issue Date: 4/27/2006
Version: 11.0 (EN)-US
Page: 3/9

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Throat Irritation, Dermatitis, Central Nervous System Depression, Skin Irritation, Headache, Dizziness, Nausea, Upper Respiratory Tract Irritation, Drowsiness, Vomiting, Optical Nerve Damage, Chest Tightness.
Delayed Effects	: No known delayed effects.
Immediate Effects	: Asphyxia.
Chronic Effects	: Methyl alcohol may be fatal or cause blindness if swallowed. Because of defatting properties, repeated skin contact can cause skin damage such as chap, dermatitis, inflammation and the formation of eczema.
Target Organs	: Cardiovascular System, Central Nervous System, Eyes, Gastrointestinal Tract, Respiratory System, Skin.

4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Medical Conditions Aggravated	: May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media	: Water jet.

5.2 Specific Hazards Arising from the Chemical or Mixture

Hazardous Combustion Products	: Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
Specific Hazards During Firefighting	: Flammable. Contents under pressure. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

5.3 Special Protective Actions for Fire-Fighters

Firefighting Instructions	: Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure.
Protection during Firefighting	: Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel	: No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Emergency Personnel	: Use personal protection as recommended in Section 8.

6.2 Environmental Precautions

Environmental Precautions	: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
---------------------------	---

6.3 Methods and Materials for Containment and Cleaning up

Containment Procedures	: Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents.
Cleanup Procedures	: Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
Other Information	: Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned.

SAFETY DATA SHEET

Part No. P5718CT (Aerosol)

Print Date: 11/11/2022
 Revision Date: 11/11/2022
 Supersedes Date: 10/25/2019
 Issue Date: 4/27/2006
 Version: 11.0 (EN)-US
 Page: 4/9

Hoppe's 9 Blast & Shine Firearm Action Grease Remover

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Prohibited Materials : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling

General Handling Precautions : KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.

Hygiene Recommendations : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

7.2 Conditions for Safe Storage Including Any Incompatibilities

Storage Requirements : Storage of individual cans should be done in an area below 55°C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended.

Incompatibilities : Segregate storage away from materials indicated in Section 10.

NFPA 30B Classification : This product is classified as a Level 2 Aerosol per NFPA 30B

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

Carbon Dioxide (124-38-9)		
ACGIH	ACGIH OEL TWA	5000 ppm
ACGIH	ACGIH OEL Ceiling	30000 ppm
OSHA	OSHA PEL (TWA) [1]	9000 mg/m ³
OSHA	OSHA PEL (TWA) [2]	5000 ppm
NIOSH	IDLH [ppm]	40000 ppm
NIOSH	NIOSH REL TWA [ppm]	5000 ppm
NIOSH	NIOSH REL STEL [ppm]	30000 ppm
California	California PEL (TWA) (mg/m ³)	9000 mg/m ³
California	California PEL (TWA) (ppm)	5000 ppm
California	California PEL (STEL) (mg/m ³)	54000 mg/m ³
California	California PEL (STEL) (ppm)	30000 ppm

Acetone (67-64-1)		
ACGIH	ACGIH OEL TWA	250 ppm
ACGIH	ACGIH OEL Ceiling	500 ppm
OSHA	OSHA PEL (TWA) [1]	2400 mg/m ³
OSHA	OSHA PEL (TWA) [2]	1000 ppm
NIOSH	IDLH [ppm]	2500 ppm
NIOSH	NIOSH REL TWA [ppm]	250 ppm
California	California PEL (TWA) (mg/m ³)	1200 mg/m ³
California	California PEL (TWA) (ppm)	500 ppm
California	California PEL (STEL) (mg/m ³)	1780 mg/m ³
California	California PEL (STEL) (ppm)	750 ppm
California	California PEL (Ceiling) (ppm)	3000 ppm
Biological Exposure Index	Acetone in urine, End of shift (Ns)	25 mg/l

Methyl Ethyl Ketone (78-93-3)		
ACGIH	ACGIH OEL TWA	200 ppm
ACGIH	ACGIH OEL Ceiling	300 ppm
OSHA	OSHA PEL (TWA) [1]	590 mg/m ³
OSHA	OSHA PEL (TWA) [2]	200 ppm
NIOSH	IDLH [ppm]	3000 ppm
NIOSH	NIOSH REL (TWA)	590 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	200 ppm
California	California PEL (TWA) (mg/m ³)	590 mg/m ³

SAFETY DATA SHEET

Part No. P5718CT (Aerosol)

Print Date: 11/11/2022
Revision Date: 11/11/2022
Supersedes Date: 10/25/2019
Issue Date: 4/27/2006
Version: 11.0 (EN)-US
Page: 5/9

Hoppe's 9 Blast & Shine Firearm Action Grease Remover

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methyl Ethyl Ketone (78-93-3)

California	California PEL (TWA) (ppm)	200 ppm
California	California PEL (STEL) (mg/m3)	885 mg/m ³
California	California PEL (STEL) (ppm)	300 ppm
Biological Exposure Index	MEK in Urine, End of shift	2 mg/l

Methyl Acetate (79-20-9)

ACGIH	ACGIH OEL TWA	200 ppm
ACGIH	ACGIH OEL Ceiling	250 ppm
OSHA	OSHA PEL (TWA) [1]	610 mg/m ³
OSHA	OSHA PEL (TWA) [2]	200 ppm
NIOSH	IDLH [ppm]	3100 ppm
NIOSH	NIOSH REL (TWA)	610 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	200 ppm
NIOSH	NIOSH REL (STEL)	760 mg/m ³
NIOSH	NIOSH REL STEL [ppm]	250 ppm
California	California PEL (TWA) (mg/m3)	610 mg/m ³
California	California PEL (TWA) (ppm)	200 ppm
California	California PEL (STEL) (mg/m3)	760 mg/m ³
California	California PEL (STEL) (ppm)	250 ppm

8.2 Exposure Controls

Engineering Measures	: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
Personal Protective Equipment	
Eye / Face Protection	: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
Hand Protection	: Chemical-resistant gloves, tested according to ASTM F903 - 17.
Remarks	: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.
Skin and Body Protection	: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
Respiratory Protection	: Respiratory protection is not anticipated to be needed.
Compliance	: If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.
Other Protective Equipment	: Safety showers and eye-wash stations should be available in the workplace near where the material will be used.
Environmental Exposure Controls	: Avoid release to the environment.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 55.80 °C	Melting / Freezing Point	> -99.00 °C
Flash Point, Liquid	> -18.00 °C	Flash Point, Propellant	Non flammable
Explosive Limits	LEL: 1.00 UEL: 36.00 vol % (v/v%)	Autoignition Temperature, Liquid	> 403.89 °C
Flammability	Flammable Aerosol	Density	0.818 g/cm ³
Molecular Weight	Not Available	Weight	6.830 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBac=1)	Not Available
Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Pressurized Product	Heat Of Combustion	11511.63 BTU/lb
Appearance / Color	Colorless	Water Solubility	Not Available
Odor	Slight	Decomposition Temperature	Not Available

SAFETY DATA SHEET

Part No. P5718CT (Aerosol)

Print Date: 11/11/2022
Revision Date: 11/11/2022
Supersedes Date: 10/25/2019
Issue Date: 4/27/2006
Version: 11.0 (EN)-US
Page: 6/9

Hoppe's 9 Blast & Shine Firearm Action Grease Remover

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2 Environmental Properties

Percent Volatile	97.00 % wt	VOC Regulatory	641.92 g/L (5.36 lbs/gal)
Percent VOC	8.02 % wt	VOC Actual	65.67 g/L (0.55 lbs/gal)
Percent HAP	0.02 % wt	HAP Content	0.16 g/L (0.00 lbs/gal)
Global Warming Potential	0.40 GWP	Maximum Incremental Reactivity	0.4479 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

10.2 Chemical Stability

Chemical Stability : This product is stable.

10.3 Possibility of Hazardous Reactions

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 Conditions to Avoid

Conditions to Avoid : Electrostatic Discharge, Other Ignition Sources, Hot Surfaces, Heat, Flames, Sparks.

10.5 Incompatible Materials

Materials to Avoid : Strong Oxidizing Agents, Strong Reducing Agents, Alkali Metals, Strong Acids, Potassium t-Butoxide, Hydrogen Peroxide.

10.6 Hazardous Decomposition Products

Thermal Decomposition : Oxides of carbon, Aldehydes, Formaldehyde, Methanol, Acetic Acid.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

Acetone (CAS: 67-64-1 / EC: 200-662-2)

LD50 Oral (Rat)	5800 mg/kg (Sigma-Aldrich)
LD50 Dermal (Rabbit)	20000 mg/kg (IUCLID)
LC50 Inhalation (Rat)	76 mg/l/4h (GESTIS Substance Database)

Methyl Ethyl Ketone (CAS: 78-93-3 / EC: 201-159-0)

LD50 Oral (Rat)	2737 mg/kg (Sigma-Aldrich)
LD50 Dermal (Rabbit)	6480 mg/kg (RTECS)
LC50 Inhalation (Rat)	205 mg/l/4h (ChemInfo)
LC50 Inhalation (Rat)	30200 ppm/4h (ChemInfo)

Methyl Acetate (CAS: 79-20-9 / EC: 201-185-2)

LD50 Oral (Rat)	6970 mg/kg (Lit.)
LD50 Dermal (Rabbit)	> 5000 mg/kg (RTECS)
LC50 Inhalation (Rat)	> 49.28 mg/l/4h (External SDS)
LC50 Inhalation (Rat)	16000 – 32000 (ChemInfo)

Routes Of Exposure : Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.

Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure : See Section 4.2

Skin Corrosion/Irritation : Not classified

Eye Damage/Irritation : Causes serious eye irritation.

Respiratory or Skin Sensitization : Not classified

SAFETY DATA SHEET

Part No. P5718CT (Aerosol)

Print Date: 11/11/2022
 Revision Date: 11/11/2022
 Supersedes Date: 10/25/2019
 Issue Date: 4/27/2006
 Version: 11.0 (EN)-US
 Page: 7/9

Hoppe's 9 Blast & Shine Firearm Action Grease Remover

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Not classified
STOT-Single Exposure	: May cause drowsiness or dizziness.
STOT-Repeated Exposure	: Not classified
Aspiration Hazard	: Not classified
Vaporizer	: Aerosol
Carcinogen Data	: None of the ingredients in the product are listed with OSHA, IARC, NTP or ACGIH as being a suspected or known carcinogen in a concentration greater than 0.1% by weight.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity and Ecological Properties

Carbon Dioxide (124-38-9)	
Log Pow	0.83

Acetone (67-64-1)	
LC50 Fish	5540 mg/l Rainbow Trout - 96hr
LC50 Fish	8300 mg/l Bluegill Sunfish - 96h
EC50 Daphnia	8800 mg/l Water Flea - 48hr
Persistence and Degradability	Biodegradability 90% / 28 days.
Biochemical Oxygen Demand	1.43 g O ₂ /g substance
Chemical Oxygen Demand	1.92 g O ₂ /g substance
Theoretical Oxygen Demand	2.2 g O ₂ /g substance
BCF Fish	0.69
BCF Other Aquatic Organisms	3
Log Pow	-0.24

Methyl Ethyl Ketone (78-93-3)	
LC50 Fish	3130 – 3320 mg/l Fathead Minnow - 96h
EC50 Daphnia	7060 mg/l Water Flea - 24hr
Persistence and Degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions.
Biochemical Oxygen Demand	2.03 g O ₂ /g substance
Chemical Oxygen Demand	2.31 g O ₂ /g substance
Theoretical Oxygen Demand	2.44 g O ₂ /g substance
Log Pow	0.3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 40 °C)
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).
Log Koc	Koc,34; Calculated value

Methyl Acetate (79-20-9)	
LC50 Fish	250 – 350 mg/l Zebra Fish - 96hr
EC50 Daphnia	1026.7 mg/l Water Flea - 48hr
EC50 Other Aquatic Organisms	> 120 mg/l Green Algae - 72hr
EC50 Other Aquatic Organisms	6100 mg/l Bacteria - 30min
Persistence and Degradability	Readily biodegradable in water. Inherently biodegradable. Highly mobile in soil.
Chemical Oxygen Demand	1511.8 mg/g
Theoretical Oxygen Demand	1510 mg/g
Biodegradation	70 % 28 Days
BCF Fish	< 1 (BCF)
Log Pow	0.18
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	0.68

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal	: Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal
----------------	--

SAFETY DATA SHEET

Part No. P5718CT (Aerosol)

Print Date: 11/11/2022
Revision Date: 11/11/2022
Supersedes Date: 10/25/2019
Issue Date: 4/27/2006
Version: 11.0 (EN)-US
Page: 8/9





Hoppe's 9 Blast & Shine Firearm Action Grease Remover

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methodologies for spent materials and residues at the time of disposition. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

- Waste Disposal Of Packaging** : In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.
- Landfill Precautions** : Not Available.
- Incineration Precautions** : **** DO NOT INCINERATE ** CONTENTS UNDER PRESSURE **.**

SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Number :	UN1950	UN1950	UN1950
14.2 UN Proper Shipping Name	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Proper Shipping Name :	Aerosols, Limited Quantity	Aerosols, Flammable, Limited Quantity	Aerosols, Limited Quantity
14.3 Transport Hazard Class(es)	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Transport Hazard Class(es) :	2.1	2.1	2.1
Labels :	None	2.1 - Flammable gas	None
Limited Quantity :	Yes 	Yes  	Yes 
EmS Code :	Not Applicable	Not Applicable	F-D, S-U
14.4 Packing Group	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Packing Group :	None	None	None
14.5 Environmental Hazards	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Marine Pollutant :	No	No	No
14.6 Special Precautions	Precautions : None Identified		
14.7 Transport in Bulk	Remarks : Not applicable for product as supplied		

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations

SARA Section 313 : Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methanol	CAS-No. 67-56-1	0.01 – 0.1%
----------	-----------------	-------------

TSCA Section 12(b) : This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D

SAFETY DATA SHEET

Part No. P5718CT (Aerosol)

Print Date: 11/11/2022
 Revision Date: 11/11/2022
 Supersedes Date: 10/25/2019
 Issue Date: 4/27/2006
 Version: 11.0 (EN)-US
 Page: 9/9

Hoppe's 9 Blast & Shine Firearm Action Grease Remover

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CERCLA Reportable Quantity : Chemical(s) subject to reporting requirements of Section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) if released to the environment at or above the reportable quantity

Acetone	CAS-No. 67-64-1	5000 lb
Methyl Ethyl Ketone	CAS-No. 78-93-3	5000 lb
Methanol	CAS-No. 67-56-1	5000 lb

15.2 State Regulations

California Proposition 65 : This product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

Methanol (67-56-1)	Developmental Toxicity	Yes	0.024 %
--------------------	------------------------	-----	---------

State Right-to-Know Lists : The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

Carbon Dioxide (124-38-9)	U.S. - New Jersey - Right to Know Hazardous Substance List
Acetone (67-64-1)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Methyl Ethyl Ketone (78-93-3)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Methanol (67-56-1)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Methyl Acetate (79-20-9)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16 - OTHER INFORMATION

Indication of changes :

Section	Changed item	Change
1	Revision date	Modified
1	Supersedes	Modified
3	Composition/Information on ingredients	Modified
9	Boiling point	Modified
9	Explosive limits (vol %)	Modified
9	Flash point	Modified
9	Relative vapor density at 20 °C	Modified
9	Density	Modified
9	Auto-ignition temperature	Modified
9	Melting point	Modified

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.